

SATELLITE MULTISWITCHES

MODEL:MS1312E

DESCRIPTION:13x12 Satellite Multiswitch



Features:

- 12 satellite IF and 1 terrestrial TV inputs for 12 satellite receiver
- 12 satellite IF inputs selected by 13V、18V 22KHz and DisEqC 2.0 signal
- Built-in amplifier
- Low insertion loss, high isolation and return loss
- SAT-IF-PATHs to the subscribers are active and supplied by the receiver
- Sheet metal housing with plastic holder
- Design good for indoor usage

Specifications

Item	Specifications	Remark
Frequency Range	Terr.:47~862MHz SAT:950~2150MHz	
Inputs	12 SAT+1 Terr.	F connectors
Outputs	12 Receiver	F connectors
Insertion Loss	Terr.	4dB
	SAT	0dB
Return Loss	Terr.	10dB
	SAT	10dB
Stop band attenuation	Terr.	25dB
	SAT	25dB
Isolation	LNB-LNB	35dB
	H/V	30dB
	REC-REC	Terr.:25dB SAT:30dB
SAT Output level	100dBμV @35dB IMA3,EN50083-3	
Terr. Output level	85dBμV @60dB IMA3,EN50083-5	
Switching Voltage	V:10~14.5V H:15~20V	
Power supply	IN:90~264V OUT:18V 2500mA	
Dimensions (w,d,h)	298x208x42	mm