

SATELLITE MULTISWITCHES

MODEL:CM58E

DESCRIPTION:5x8 Stand-alone Multiswitch



Features:

- 4 satellite IF and 1 terrestrial TV inputs for 8 satellite receivers
- 4 satellite IF inputs selected by 13V, 18V and 22KHz signal
- Built-in amplifier
- Low insertion loss, high isolation and return loss
- SAT-IF-PATHs to the subscribers are active and supplied by the receiver
- Sheet metal housing with plastic holder
- Design good for indoor usage

Specifications

Item		Specifications	Remark
Frequency Range		Terr.:47~862MHz SAT:950~2150MHz	
Inputs		4 SAT+1 Terr.	F connectors
Outputs		8 Receivers	F connectors
Insertion Loss	Terr.	2dB	
	SAT	0dB	
Return Loss	Terr.	10dB	
	SAT	10dB	
Stop Band Attenuation	Terr.	25dB	
	SAT	25dB	
Isolation	LNB-LNB	35dB	
	H/V	30dB	
	REC-REC	Terr.:25dB SAT:30dB	
SAT Output Level		100dB μ V @35dB IMA3,EN50083-3	
Terr. Output Level		85dB μ V @60dB IMA3,EN50083-5	
Switching Voltage		V:10~14.5V H:15~20V	
Power Supply		IN:90~264V OUT:18V 1600mA	
Dimensions(w,d,h)		155×120×42mm	